

Coolant



PETRONAS Tutela Coolant LL-ELC

Range:

Long description: Concentrated Long-Life Coolant for heavy duty diesel, gasoline and natural gas powered engines coolant systems. Formulated with Mono-Ethylene Glycol enhanced with a special Organic Acid salts inhibitor (OAT Technology), nitrites and molybdates, free of nitrates, borates, phosphates, silicates and amines. Excellent protection against overheating, frost and corrosion.

For construction, quarrying, mining and agricultural machineries or heavy-duty engine coolant systems where a ELC or OAT coolant technology is required; specifically developed for Caterpillar machineries

Industry Specifications: ASTM D3306 ASTM D4985 ASTM D6210 AS/NZS 2108.1:1997 "Type A" International Truck & Engine CEMS B-1 JIS K 2234 SAE J1034

OEM Performance - Only for Automotive: CAT ELC/EC-1 Cummins Bulletin 3666132 & 14603 Detroit Diesel 7SE298 & 93K217 Freightliner 48-22880 General Motors 1825M, 1899M, Heavy Truck John Deere JDM H24 Kenworth R026-170-97 Land Rover Mack Truck 014GS17004 MAN 324 MB DBL 7700 MTU MTL 5048 PACCAR CS0185 Peterbilt 8502.002 Scania TB1451 TMC RP 329 Volvo

Application(s) - For Consumers pages: Agricultural Equipment, Construction; Quarry & Mining, Heavy-Duty Vehicle (HD)